

time switch, digital, Expert 4 channels, year, 85V...230V 6MW



Model	
Product brand name	SETRON
Product designation	Time-delay switch
Design of the product	Digital time switch Expert
Design of the switching function	CO contact
General technical data	
Manner of function	
• radio-controlled	No
• line-synchronous	No
• quartz-controlled	No
Accuracy / per day	0.2 s
Shortest switching time interval / of channel 1	1 s
Voltage	
Control voltage / at AC / rated value	
• minimum	102 V
• maximum	253 V
Overvoltage category / acc. to IEC 61010-1	III

Supply voltage	
Operating voltage / at AC / rated value	250 V
Type of voltage / of the supply voltage	AC
Supply voltage frequency	
• maximum	60 Hz
• minimum	50 Hz
Protection class	
Protection class IP	IP20
Switching capacity	
Switching capacity current / at AC / at 250 V / Rated value	16 A
Dissipation	
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	2.5 W
Product details	
Product feature	
• external switch input	No
• floating switching contact	Yes
Product function	
Product function	
• 60 min time program	Yes
• Astro program	Yes
• Automatic daylight-saving adjustment	No
• Operating hours counter	Yes
• direct operation	Yes
• Holiday time program	Yes
• Impulse program	No
• annual time program	Yes
• Switching preselection	Yes
• 24-hour time program	Yes
• Text guidance in display	Yes
• Weekly time program	Yes
• Random time program	No
• Cyclical time program	No
Number	
Number of terminals / with cross-head screw	1
Number of channels	4
Number of memory slots	336
Connectable conductor cross-section / in main circuit	
• for rigid conductor / maximum	4 mm ²

- for rigid conductor / minimum 1.5 mm²
- for flexible conductor / with core end processing / maximum 2.5 mm²

Mechanical Design

Height	83 mm
Width	36 mm
Depth	64 mm
Number of width units	6
Mounting type	DIN rail

Environmental conditions

Ambient temperature / minimum permissible	-20 °C
Ambient temperature / maximum permissible	55 °C
Ambient temperature / during storage	
• minimum	-20 °C
• maximum	60 °C

Certificates

Reference code	
• acc. to DIN EN 61346-2	K
• acc. to DIN EN 81346-2	K

General Product Approval	Declaration of Conformity	other
--------------------------	---------------------------	-------



VDE



EG-Konf.

[Environmental Confirmations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7LF4444-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7LF4444-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7LF4444-0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

